

CROSS MOBILE LIFT



PRODUCT SPECIFICATIONS

Fully self-propelled 6-meter electric drive (steel track) configuration list, fully self-propelled 8-meter electric drive (steel track), fully self-propelled 10-meter electric drive (steel track) configuration list, fully self-propelled 12-meter electric drive (steel track) configuration list, fully self-propelled 14-meter electric drive + one-button leveling + (steel track) configuration list, fully self-propelled 14-meter configuration list, fully self-propelled small 4-meter configuration list, fully self-propelled small 6-meter configuration list, fully self-propelled narrow 0810 configuration list

If you don't understand, please call us.: 1528903273



MATERIAL

Safety guardrail	35mm*35mm square tube
mesa	Anti-slip pattern plate
Support rod	Material: Q345
Base	Q235 steel plate welding
Lifting cylinder	1 piece
Outrigger Cylinder	4 sticks
Power battery	Tianneng
Hydraulic oil	32/46
Electronic control system	HBL
Motor Controller	Trinity
Track chassis	Steel tracks
Motor pump	Guo Rui
Valve Group	Fubo Norma
Surface treatment	Shot blasting, rust removal, plastic spraying

CROSS MOBILE LIFT

PRODUCT CONFIGURATION

Proportional control	Braking system	Oil pipe explosion-proof system	Extended platform
Troubleshooting	Emergency descent	Safety maintenance support	Charging protection system
Emergency stop switch	One-click leveling	Tilt protection system	Folding guardrail
buzzer	trumpet	ECU (three in one)	PCU (nine-button button)

BASIC PARAMETERS OF THE PRODUCT

BASIC PARAMETERS	UNIT	MPZXLD-0608
Safe working load	Kg	320
Extended platform safe working load	Kg	113
Maximum working height	m	8.8
Maximum platform height	m	6
Machine length	mm	2780
Machine width	mm	1570
Overall height (guardrails not folded)	mm	2350
Overall height (guardrail folded)	mm	1780
Working platform size	mm	2270X1130
Platform extension size	mm	900
Minimum ground clearance (folded state)	mm	0
Minimum ground clearance (lifting state)	mm	0
Minimum turning radius	mm	0
Lifting motor	V/Kw	48V/4.5KW
Travel motor	V/Kw	48V/4KW
Equipment travel speed (folded state)	Km/h	1.8
Equipment travel speed (lifting state)	Km/h	0
Ascent/descent speed	sec	80/35
Battery	V/Ah	8x12v/240Ah
charger	V/A	48/30
Maximum climbing ability	%	25
Maximum allowable working angle	°	1.5-3
Machine weight	Kg	2770