

# EPDM Soft And Hard Composite Sealing Strip

## Soft and hard composite sealing strip series

### Introduction

EPDM soft and hard composite sealing strip is a sealing material made of EPDM rubber (EPDM) and hard materials (such as plastic, metal, etc.). It combines the advantages of both soft and hard materials, with the good elasticity and weather resistance of EPDM rubber and the stability and wear resistance of hard materials. It is suitable for sealing and sound insulation of various doors and windows.

### Specification

#### Material

Composite material of EPDM and hard material.

#### Size

Common sizes include width 5mm - 50mm thickness 2mm - 20mm length can be customized as needed.

#### Surface Treatment

Smooth surface or textured surface to enhance sealing effect.

#### Color

Black gray white and other colors are available and can also be customized according to the color of doors and windows.

### Application Scenarios

- Residential Doors and Windows: Suitable for wooden doors, aluminum alloy windows, and PVC windows, providing good sealing and sound insulation to maintain a comfortable indoor environment.
- Commercial Buildings: Suitable for stores, office buildings, hotels, etc., offering sound insulation and thermal insulation to improve indoor comfort.
- Industrial Buildings: Suitable for factories, workshops, etc., providing wear-resistant, weather-resistant seals to keep the indoor environment clean and quiet.



Hengou Automotive Seals

+86 133 6375 2608  
+86 151 9491 7757

+86 133 6375 2608  
+86 151 9491 7757

#### Raw Material Inspection

Strict inspection, quality standards

#### Production Process Control

Strict implementation

#### Finished Product Inspection

Quality standards

#### Performance Testing

Resistant to low temperature, aging, etc.

### Installation Method

1. Clean the installation surface: Make sure the surface of the door and window frame notch is clean, dry, and free of oil and dust.
2. Measurement and cutting: Measure and cut the sealing strip according to actual needs to ensure the appropriate length.
3. Press-in installation: Press the sealing strip into the notch of the door and window frame to ensure that the sealing strip fits tightly with the notch.

+86 133 6375 2608  
+86 151 9491 7757

info@ho-sealingstrip.com