
Warehouse Door Seals

Door and window sealing strip series

Introduction

Warehouse door sealing strips are sealing materials specially designed for warehouse doors. They are installed around the door to fill the gap between the door and the door frame to prevent cold wind, dust, insects and moisture from entering the warehouse, while improving the airtightness and sound insulation of the door.





Specification

Material

Rubber polyurethane PVC etc.

Size

Common sizes include width 100mm - 300mm thickness 10mm - 30mm length can be customized as needed.

Surface Treatment

Smooth surface or textured surface to enhance sealing effect.

Color

Black gray blue and other colors are availableand can also be customized according to customer needs.

Applicable Scenarios

Warehouse door seals are suitable for all types of warehouse doors, such as rolling doors, swing doors, sliding doors, etc. It is widely used in warehouse doors in the fields of warehousing, logistics, industrial manufacturing, etc., effectively preventing the external environment from affecting the goods and equipment inside the warehouse, and ensuring the stability and safety of the internal environment of the warehouse.
























Strict implementation



Finished Product Inspection Quality standards

Raw Material Inspection Strict inspection, quality standards

> **Performance Testing** Resistant to low temperature, aging, etc.

Precautions

- 1. During installation, ensure that the sealing strip fits the door frame tightly to avoid gaps to ensure a good sealing effect.
- 2. The length of the sealing strip should match the length of the door frame to avoid poor sealing due to being too long or too short.
- 3. Check the adhesion of the sealing strip regularly and replace it in time if it is loose or falling off.