Lip Seal The series of container lid sealing strips

Introduction

Lip seal is a rubber strip used for sealing doors and windows. Its cross section is lip-shaped and has good sealing performance. It is installed at the notch of the door and window frame to prevent air, water vapor and noise from penetrating into the room through the gap of the door and window, thus improving the indoor sound insulation and heat preservation effect.



Specification

Material

EPDM rubber silicone and other weather-resistant and aging-resistant materials

Size

Common sizes include width 5mm - 30mm thickness 2mm -10mm length can be customized as needed.

Color

Smooth surface or textured surface to enhance sealing effect.

Surface Treatment

Black gray white and other colors are available and can also be customized according to the color of doors and windows.

Finished Product Inspection Quality standards

Applicable Scenarios

Lip seals are suitable for various doors and windows, such as wooden doors, aluminum alloy doors and windows, plastic steel doors and windows, etc. It is widely used in places such as homes, commercial buildings and industrial buildings to keep the indoor environment dry, quiet and comfortable.



Hengou Automotive Seals





6

+86 133 6375 2608

+86 151 9491 7757



9




+86 133 6375 2608

+86 151 9491 7757



1. During installation, ensure that the seal fits tightly with the notch of the door and window frame to avoid gaps to ensure a good sealing effect.

2. The length of the sealing strip should match the length of the notch of the door and window frame to avoid poor sealing effect due to excessive length or shortness.



Raw Material Inspection

Strict inspection, quality standards

Production Process Control

Strict implementation

3. Check the use status of the sealing strip regularly. If aging, hardening or damage is found, it should be replaced in time to maintain the sealing effect.

Performance Testing Resistant to low temperature, aging, etc.

