

Nitrile Rubber Sealing Strip

 [The series of rubber sealing strips](#)

Introduction

Nitrile rubber sealing strip is a sealing product made of nitrile rubber (NBR) material. NBR sealing strip has excellent oil resistance, wear resistance and weather resistanc.

Specification

Material

Nitrile rubber (NBR).

Density

0.9 g/cm³ - 1.6 g/cm³
(customizable)

Size

Common sizes include width of 5mm - 50mm thickness of 2mm - 10mm and length can be customized according to requirements.

Surface Treatment

Smooth surface or textured surface to enhance sealing effect.




Color

Black gray white and other colors are available and can also be customized according to needs.





Applicable Scenarios

Nitrile rubber sealing strips are widely used for sealing and protection in the fields of automobiles, mechanical equipment, industrial pipelines, etc., mainly used to prevent the leakage of liquids, gases and dust, and improve the sealing performance and safety of equipment.



Hengou Automotive Seals

 +86 133 6375 2608
+86 151 9491 7757

 +86 133 6375 2608
+86 151 9491 7757

Raw Material Inspection

Strict inspection, quality standards

Production Process Control

Strict implementation

Finished Product Inspection

Quality standards

Performance Testing


Resistant to low temperature, aging, etc.


Installation Method

1. Clean the installation surface: Ensure that the installation surface is clean, dry, free of oil and dust.

2. Measure and cut: Measure and cut the sealing strip according to actual needs to ensure the appropriate length.

3. Press-in installation: Press the sealing strip into the installation groove or fit the sealing surface to ensure that the sealing strip fits tightly with the surface.

 +86 133 6375 2608
+86 151 9491 7757

 info@ho-sealingstrip.com