
Self-adhesive Sealing Strip For Wooden Doors

Door and window sealing strip series

Introduction

The self-adhesive sealing strip for wooden doors is a sealing material specially designed for wooden doors. It has a self-adhesive backing and is easy to install on the edge of the wooden door or door frame. It is used to fill the gap between the door and the door frame to prevent cold wind, dust and noise from entering the room, while improving the sealing and sound insulation of the door.





Specification

Material

Rubber silicone polyurethane etc.

Common sizes include width

5mm - 20mm thickness 3mm -

10mm length can be customized

Size

as needed.

Surface Treatment

Smooth surface or textured surface to enhance sealing effect.

Color

Black gray blue and other colors are availableand can also be customized according to customer needs.

Raw Material Inspection

Strict inspection, quality standards

Finished Product Inspection Quality standards

Applicable Scenarios

Wooden door self-adhesive sealing strips are widely used in the sealing and sound insulation of wooden doors in homes, offices, hotels, etc. It can effectively prevent cold wind, dust and noise from entering the room and improve indoor comfort.









1

+86 133 6375 2608

+86 151 9491 7757




9




+86 133 6375 2608

+86 151 9491 7757



1. Make sure the door frame surface is clean and dry during installation to ensure that the sealing strip can be firmly pasted. 2. Avoid stretching or squeezing the sealing strip during pasting to avoid affecting its sealing effect.





Hengou Automotive Seals

Production Process Control

Strict implementation

Performance Testing

Resistant to low temperature, aging, etc.

3. Check the adhesion of the sealing strip regularly. If it is found to be loose or falling off, replace it in time.

