



Anchor Bolt Series

EQUAL-STRENGTH RIBBED REBAR RESIN BOLT

Applied for roadway and stope support, restraining rock deformation and ensuring operation safety. Manufactured from HRB335-600 right-hand rebar with full-length equal-strength design. Delivers high anchoring force and excellent reliability when matched with resin anchoring cartridges.



PRODUCT PARAMETERS

Specification	Yield Strength (MPa)	Tensile Strength (MPa)	Elongation (%)	Yield Load (KN)	Tensile Load (KN)
Φ16	≥ 335	≥ 455	≥ 15	≥ 69	≥ 92
Φ18	≥ 335	≥ 455	≥ 15	≥ 87	≥ 116
Φ20	≥ 335	≥ 455	≥ 15	≥ 108	≥ 143
Φ22	≥ 335	≥ 455	≥ 15	≥ 131	≥ 173
Φ16	≥ 400	≥ 540	≥ 16	≥ 81	≥ 109
Φ18	≥ 400	≥ 540	≥ 16	≥ 102	≥ 138
Φ20	≥ 400	≥ 540	≥ 16	≥ 126	≥ 170
Φ22	≥ 400	≥ 540	≥ 16	≥ 152	≥ 206
Φ16	≥ 500	≥ 630	≥ 15	≥ 101	≥ 127
Φ18	≥ 500	≥ 630	≥ 15	≥ 128	≥ 161
Φ20	≥ 500	≥ 630	≥ 15	≥ 158	≥ 198
Φ22	≥ 500	≥ 630	≥ 15	≥ 191	≥ 240