


Machine Tool Series

· Jack

TQ ANCHOR CABLE DE-ANCHORING TOOL



The TQ type anchor cable de-anchoring tool is a special hydraulic equipment for underground coal mines. With a rated oil pressure of 63MPa, it has strong and stable de-anchoring force. Suitable for various specifications of steel strands, it is easy to operate and efficient in de-anchoring, assisting in anchor device recovery and roof safety, and applicable to roadway support operations.



PRODUCT PARAMETERS

Model	Rated De-anchoring Force (kN)	Rated Pressure (MPa)	Applicable Nominal Diameter of Steel Strand (mm)	Center Hole Diameter (mm)	System Rated Working Pressure (MPa)	Effective Oil Tank Volume (L)	Machine Weight (kg)
TQ18-300/55	300	55	18	20	57	4	27
TQ18-350/60	350	60	18	20	62	4	27
TQ19-300/55	300	55	19	22	57	4	27
TQ19-400/60	400	60	19	22	62	4	27
TQ22-250/55	250	55	22	24	57	4	27
TQ22-400/63	400	63	22	24	64	4	27
TQ22-500/63	500	63	22	24	64	4	27
TQ22-550/63	550	63	22	24	64	4	27
TQ22-700/63	700	63	22	24	64	4	27
TQ22-500/63	500	63	29	32	64	4	27
TQ22-600/63	600	63	29	32	64	4	27