

Conveyor Series

MOBILE BELT CONVEYOR



MODEL ZP60 MOBILE CONVEYOR

The Model ZP60 mobile conveyor is suitable for use in mines, factories, construction sites, stations, docks, and similar sectors, and is designed for the conveyance of loose bulk materials or packaged goods.

Body Length	10m	12m	15m
Conveyor Belt Width (mm)	500	500	500
Conveyor Belt Speed (m/s)	1.5	1.5	1.5
Lifting Height (mm)	4200	5300	6900
Max. Inclination Angle of Frame	19°	19°	19°
Conveying Capacity (t/h)	70-120	70-120	70-120
Tensioning Stroke (mm)	300	300	300
Motor Power (KW)	3.0	4.0	4.0
Body Width (mm)	690	690	690

TDSL1 / TDSO SERIES — MOBILE TYPE

This equipment is ideal for short-distance transport and variable-route handling, including palletizing and warehousing, of bulk materials and packaged goods at docks, warehouses, coal yards, construction sites, and grain depots. Its pneumatic tires reduce rolling resistance for easy mobility, ensuring reliable operation with low noise. The lifting mechanism, available in electric and manual options, features a worm gear structure, offering an attractive design, lightweight build, and low maintenance needs.

Body Length	6m	8m	10m	12m	15m
Conveyor Belt Width (mm)	500-650	500-650	500-650	500-650	500-650
Conveyor Belt Speed (m/s)	1.6	1.6	1.6	1.6	1.6
Lifting Height (mm)	3700	3700	4500	5600	7000
Max. Inclination Angle of Frame	19°	19°	19°	19°	19°
Tensioning Stroke (mm)	300	300	300	300	300
Motor Power (KW)	3.0	3.0	4.0	4.0	6-pole 4.0
Lifting Motor Power (KW)	-	-	0.75	1.0	1.5
Body Width (mm)	690-840	690-840	690-840	690-840	690-840
Conveying Capacity (t/h)	60-100	60-100	60-100	60-100	60-100