

Anchor Bolt Series

SPLIT SET ROCK BOLT

A high-efficiency support product for mines, tunnels and geotechnical engineering, made of high-strength steel through special processing. It uses the expansion elasticity of the tube to fit closely with surrounding rock after installation, providing rapid radial support and restraining deformation. Featuring easy installation, stable bearing capacity and strong pull-out resistance, it adapts to various rock conditions and is widely used for temporary and permanent underground support.



PRODUCT PARAMETERS

Model (MF)	Outer Diameter d (mm)	Bar Length L (mm)	Wall Thickness δ (mm)	Slot Width b (mm)	Recommended Drilling Diameter (mm)	Material
MF30	30	1400/1600/1800/2000	2.5-3.0	12.5-15.5	28-29	Q235 / Q355
MF33	33	1400/1600/1800/2000	2.7-3.2	12.5-15.5	31-32	Q235 / Q355
MF35	35	1600/1800/2000/2200	2.8-3.3	12.5-15.5	33-34	Q235 / Q355
MF40	40	1600/1800/2000/2200	3.0-3.5	12.5-15.5	38-39	Q235 / Q355
MF43	43	1800/2000/2200/2500	3.0-3.5	12.5-15.5	41-42	Q235 / Q355
MF45	45	2000/2200/2500	3.2-3.8	12.5-15.5	43-44	Q355