

Machine Tool Series · Jointer

MINE ANCHOR MESH JOINTER

The mine anchor mesh jointer is a special equipment for coal mine roadway support. It is easy to operate, has a firm buckle, quickly connects the anchor mesh and anchor bolts, is dust and vibration resistant, suitable for underground working conditions, and improves support efficiency and operation safety.



PRODUCT PARAMETERS

Model	Minimum Starting Air Pressure (MPa)	Maximum Working Air Pressure (MPa)	Normal Working Air Pressure (MPa)	Maximum Number of Nails Loadable (pieces)	Tensile Strength of Buckle Nail (N/mm ²)	Formed Inner Diameter of Buckle Ring at 0.6MPa (mm)	Nailing Frequency (times/minute)	Net Weight (kg)
LWQ - 7	0.35	0.8	0.6 - 0.8	50	700 - 850	6-7	120	1.5
LWQ - 8	0.35	0.8	0.6 - 0.8	55	700 - 850	7-8	120	1.6
LWQ - 9	0.35	0.8	0.6 - 0.8	60	700 - 850	8-9	120	1.77
LWQ - 10	0.35	0.8	0.6 - 0.8	60	700 - 850	9-10	120	1.78
LWQ - 11	0.35	0.8	0.6 - 0.8	60	700 - 850	10-11	120	1.8
LWQ - 12	0.35	0.8	0.6 - 0.8	70	1700 - 1850	11-12	120	2.1
LWQ - 13	0.35	0.8	0.6 - 0.8	80	1700 - 1850	12-13	120	2.4
LWQ - 15	0.35	0.8	0.6 - 0.8	90	1700 - 1850	14-15	120	2.9
LWQ - 18	0.35	0.8	0.6 - 0.8	95	1700 - 1850	17-18	120	3.3
LWQ - 20	0.35	0.8	0.6 - 0.8	100	1700 - 1850	19-20	120	3.65