

Drill Pipe Series · Pneumatic drill rod

JUMBO DRILL PIPE

Specially designed for mine jumbo drilling, the mine jumbo drill pipe is made of high-strength alloy steel, with wear resistance and impact resistance. The rod body diameter ranges from 26mm to 89mm, with customizable length and various threaded connections, compatible with different jumbo equipment. Suitable for drilling in hard rock, coal seams, etc., it is efficient and stable, ensuring the safety of mine mining, tunnel construction and other operations, and extending service life.



PRODUCT PARAMETERS

Spiral Diameter	Rod Diameter	Joint	Theoretical Torque	Reference Drilling Depth	Matching Drilling Rig	Drill Bit Diameter
Φ28mm	Φ18mm	F12 M16	150-200N.m	1-10m	ZQSJ-50/1.6 ZQSJ-65/2.5 ZQSJ-90/2.4 ZQSJ-100/2.5 ZQSJ-140/4.1 ZQJC-160/4.6	Φ43mm
Φ30mm	Φ18mm	F12 M18	150-200N.m	1-15m		Φ43mm
Φ38mm	Φ21mm	F14 Tr16	150-350N.m	5-30m		Φ43mm
Φ40mm	Φ22mm	F14 Tr16	150-350N.m	5-30m		Φ43mm
Φ67mm	Φ27mm	F18 F24	250-350N.m	10-120m		Φ76mm
Φ69mm	Φ27mm	F18 F24	250-350N.m	10-120m		Φ76mm
Φ72mm	Φ32mm	F24 F26	350-450N.m	50-120m		Φ82、84mm
Φ75mm	Φ34mm	F24 F26	350-450N.m	50-120m		Φ89、94mm
Φ89mm	Φ50mm	F24 F32	350-450N.m	50-150m	ZDY-1200 ZDY-1500 ZDY-1900 ZDY-4000	Φ110mm
Φ98mm	Φ73mm	B41 B45	10000-12000N.m	100-300m		Φ110、120mm
Φ100mm	Φ60mm	B41 B45	8000-12000N.m	100-220m		Φ113、125mm
Φ113mm	Φ73mm	B41 B45	8000-12000N.m	100-300m		Φ133、146mm