

Conveyor parts

· Protection Switch Series

BIDIRECTIONAL PULL ROPE SWITCH

- High-strength aluminum alloy precision die-cast housing, providing strong impact resistance.
- High housing protection level, excellent sealing, dustproof, waterproof, and condensation-proof.
- Dual switch outputs, large contact capacity, sensitive

operation, and reliable performance.

- Plastic-coated steel wire rope is moisture-proof, acid and alkali resistant, and flame-retardant.
- Comes with an extra-large junction box, supporting customer function upgrades.



Two-way pull cord switch



Indicator light two-way pull cord switch



Stainless steel pull cord switch



Balanced bidirectional pull cord switch

PRODUCT PARAMETERS

Model	Actuating Force	Contact Capacity	Protection Class	Operating Voltage	Installation Spacing	Reset Mode	Applicable Belt Width	Drawing No. Reference
KLT2- II	30~50N	AC220V/380V 5A	IP65	AC220V/380V/ DC24V	20~30m	Manual / Automatic	500~1800mm	TD1LS1.1
HFKLT2- II	30~50N	AC220V/380V 5A	IP65	AC220V/380V/ DC24V	20~30m	Manual / Automatic	500~1800mm	TD2LS1.1
JLK4-S	30~60N	AC220V/380V 5A	IP67	AC220V/380V/ DC24V	20~30m	Manual / Automatic	500~1800mm	TD3LS1.1
EXKLT2- II	30~50N	AC220V/380V 5A	IP65	AC220V/380V/ DC24V	20~30m	Manual / Automatic	500~1800mm	TD4LS1.1