

PRESSURE VESSEL
TANKER TRAILER

60.72 m³ LPG
(Commercial Propane)
Transport Semi-trailer



CONFIG

- **Bare Tank:** Utilizes a high-strength, lightweight structure, resulting in lower weight due to the absence of covering, specifically designed for efficient transportation of conventional media.
- **Ladder Configuration:** Rear-mounted and detachable, standard with anti-slip design and a top-folding safety grab handle.
- **Standard air suspension axles to meet actual customer needs.**
- **Aluminum alloy wheels reduce weight and save fuel.**
- **Two valve boxes (left and right), two sets of unloading system valves, and a separate top loading system for easier operation.**
- **Level gauge**
- **Safety valve**

PRODUCT DETAILED PARAMETERS

Filling Medium	LPG (Liquefied Petroleum Gas)— Commercial Propane LPG (Commercial Propane-Butane Mixture) — Propane	Material	Q420DR
Design Pressure	1.76/-0.04Mpa	Design Temperature	-40/50℃
Geometric Volume	60.72m3	Curb Weight	14498kg
Load Capacity	25502kg	Gross Vehicle Weight	40000kg
Overall Dimensions (L x W x H)	13400*2550*4000mm	Saddle Height Saddle Load Capacity	1240/16000mm/kg
It is recommended to use a tractor.	6x4 Permissible Towing Mass ≥ 40 tons		