

LIQUID TANKER TRAILER

*Liquid Food
Transport Semi-trailer*



Edible Oil Transport Semi-trailer

JGY9402GSY

CONFIG

- **Customizable Capacity (20m³ - 60m³+) :** We provide optimized payload solutions tailored to the specific density of the transported medium and local weight restrictions.
- **Insulation Tank:** Available with an optional high-density insulation layer and stainless steel or aluminum cladding, delivering excellent temperature control performance to meet various constant-temperature transport requirements.
- **Versatile Valve Selection:** Supports pneumatic foot valves, ball valves, or butterfly valves; material options include stainless steel or corrosion-resistant plastic lining.
- **Toolbox Configuration:** Flexible positioning (left, right, or center); features high-strength sealing for waterproof and anti-theft protection.
- **Multifunctional Access Ladder:** Available in front-mounted or rear-mounted configurations; comes standard with a non-slip design and a foldable safety handrail at the top.
- **Side protection**

// PRODUCT DETAILED PARAMETERS



Model

JGY9402GSY



Overall
Dimensions (mm)

11700 × 2550, 2500 × 3900



Volume (m³)

Actual: 43
Total Capacity: 37.1
Effective Volume: 35.51



Medium

Edible Oil



Curb Weight (kg)

7680; 7500; 7000



Tank Dimensions(mm)

Before Insulation: 11142 × Ø2100 (Front) / Ø2350 (Rear)
After Insulation: 11342 × Ø2300 (Front) / Ø2550 (Rear)
After Insulation: 11302 × Ø2260 (Front) / Ø2510 (Rear)
After Insulation: 11242 × Ø2200 (Front) / Ø2450 (Rear)