

LIQUID

TANKER TRAILER

Standard Liquid Transport
Semi-trailer



JGY9400GPG

CONFIG

- **Customizable Capacity (20m³ - 60m+):** We provide optimized payload solutions tailored to the specific density of the transported medium and local weight restrictions.
- **Insulated Tank:** Available with an optional high-density insulation layer and stainless steel or aluminum cladding, delivering excellent temperature control performance to meet various constant-temperature transport requirements.
- **Versatile Valve Selection:** Supports pneumatic foot valves, ball valves, or butterfly valves; material options include stainless steel or corrosion-resistant plastic lining.
- **Toolbox Configuration:** Flexible positioning (left, right, or center); features high-strength sealing for waterproof and anti-theft protection.
- **Multifunctional Access Ladder:** Available in front-mounted or rear-mounted configurations; comes standard with a non-slip design and a foldable safety handrail at the top.
- **Side protection**

// PRODUCT DETAILED PARAMETERS

 Model	JGY9400GPG	 Name	Standard Liquid Transport Semi-trailer
 Tank Volume (m³)	48.5m³	 Overall Dimensions(mm)	11800×2550,2510×3850
 Medium	Ordinary Liquids (Edible Oil / Kill Fluid, etc.)	 Curb Weight (kg)	6500,6300,6200,6000