



LIQUID TANKER TRAILER

Corrosive Goods
Tank Semi-trailer

JGY9406GFW

CONFIG

- **Customizable Capacity (20m³ - 60m⁺):** We provide optimized payload solutions tailored to the specific density of the transported medium and local weight restrictions.
- **Insulation Options:** Available as either an insulated or bare tank; optional features include a high-density insulation layer clad in stainless steel or aluminum sheeting to meet constant-temperature transport requirements.
- **Versatile Valve Selection:** Supports pneumatic foot valves, ball valves, or butterfly valves; material options include stainless steel or corrosion-resistant plastic lining.
- **Toolbox Configuration:** Flexible positioning (left, right, or center); features high-strength sealing for waterproof and anti-theft protection.
- **Multifunctional Access Ladder:** Available in front-mounted or rear-mounted configurations; comes standard with a non-slip design and a foldable safety handrail at the top.

// PRODUCT DETAILED PARAMETERS



Model

JGY9406GFW



Name

Corrosive Goods
Tank Semi-trailer



Tank Volume (m³)

38m³



Overall Dimensions(mm)

10570×2540,2500×3850



Medium

Corrosive Liquids (Sulfuric Acid
/ Hydrochloric Acid, etc.)



Curb Weight (kg)

8500