



LIQUID TANKER TRAILER

Standard Liquid Transport
Semi-trailer

JGY9403GPG

CONFIG

- **Customizable Capacity (20m³ - 60m+):** We provide optimized payload solutions tailored to the specific density of the transported medium and local weight restrictions.
- **Insulated Tank:** Available with an optional high-density insulation layer and stainless steel or aluminum cladding, delivering excellent temperature control performance to meet various constant-temperature transport requirements.
- **Versatile Valve Selection:** Supports pneumatic foot valves, ball valves, or butterfly valves; material options include stainless steel or corrosion-resistant plastic lining.
- **Toolbox Configuration:** Flexible positioning (left, right, or center); features high-strength sealing for waterproof and anti-theft protection.
- **Multifunctional Access Ladder:** Available in front-mounted or rear-mounted configurations; comes standard with a non-slip design and a foldable safety handrail at the top.
- **Side protection**

// PRODUCT DETAILED PARAMETERS



Model

JGY9405GPG



Name

Standard Liquid
Transport Semi-trailer



Tank Volume (m³)

40.7m³



Overall Dimensions(mm)

10700×2550,2510×3850



Medium

Ordinary Liquids
(Edible Oil / Kill Fluid, etc.)



Curb Weight (kg)

8200,8000,7800,7500